

**LUBE LOGIC**®

Serving industry  
since 1971



**G. P. Reeves Inc.**  
12764 Greenly Street  
Holland, MI 49424 USA

Phone: 888.399.8893  
Fax: 616.399.8867  
Web Site:  
<http://gpreeves.com>

# GPMD1513-M8 GREASE DISPENSER

PLC Compatible, nose-mountable, air-operated, single-acting, adjustable, metered shot dispenser

- Accurate repetitive dispensing of 0.02 to 0.80 cubic centimeter shots
- Dispenser can be mounted onto any 1/4" NPT Female Port
- Compressed air inlet is 1/4" Tube Push-Lock
- Eliminates oozing or dripping problems by putting the dispenser at the dispense point
- Swivel head allows dispenser ports to point in any direction
- Compact design allows this dispenser to be mounted at the dispense point or nozzle
- Change shot size quickly and easily
- Operates with low pressure grease (up to 200 p.s.i.)
- Nose mounted, requires no special manifold or base
- Output check valve prevents dripping or leaking
- Uses a positive displacement air-operated pump, two check valves, and a simple stroke adjustment mechanism to accurately deliver measured shots of grease with a 9:1 boost ratio
- Includes magnetic piston and Balluff magnetic field sensor for stroke confirmation
- Operates with 3-way NC Air Valve

